DISCLAIMER

Notice: This presentation has been provided as part of a U.S. Environmental Protection Agency webinar. The document does not constitute EPA policy. Mention of trade names or commercial products does not constitute endorsement or recommendation for use. Links to non-EPA web sites do not imply any official EPA endorsement of or a responsibility for the opinions, ideas, data, or products presented at those locations or guarantee the validity of the information provided. Links to non-EPA servers are provided solely as a pointer to information that might be useful to EPA staff and the public.



Environmental Product Declarations and Product Category Rules

Amy A. Costello, LEED-AP, LCACP Rita Schenck, PhD, LCACP October 26, 2009





Rita Schenck





- Founder & Director of IERE
- NGO that Supports Fact-based Environmental Decision-Making
- Home of the American Center for Life Cycle Assessment (ACLCA)





This session will cover

Environmental Product Declarations (EPDs)

The current and pending PCR standards globally

Product Category Rules (PCRs)

- Where they are from
- How they are written
- How they are verified

- Existing and planned EPD programs
- What is new? Meeting4-5 November





Environmental Product Declarations


- A label that discloses the life cycle environmental performance of products and services
- NOT a claim of environmental superiority
- Also Know As:
 - Type III Environmental Declarations
 - Type III Ecolabels

| Nutritio | n Facts |
|---------------------------|------------------------------------|
| Serving Size 1 cup (256.0 | 0 g) |
| Amount Per Serving | |
| Calories 376 | Calories from Fat 157 |
| | % Daily Value |
| Total Fat 17.4g | 27% |
| Saturated Fat 2.0g | 10% |
| Polyunsaturated Fat 8. | 2g |
| Monounsaturated Fat 3 | 3.3g |
| Cholesterol 0mg | 0% |
| Sodium 38mg | 2% |
| Total Carbohydrates | 28.3g 9 % |
| Dietary Fiber 10.8g | 43% |
| Protein 33.2g | |
| Vitamin A 9% | Vitamin C 124% |
| Calcium 50% | Iron 50% |
| * Based on a 2000 calorie | e diet |






Life Cycle Assessment: The Holistic Yardstick of Environmental Performance



Scoping: how and what we measure



- •Height ?
- •Circumference?
- •Shirt size?
- •Centimeters?





EPD Content Options

- A. Life cycle impact results, or
- B. Life cycle inventory results (e.g., grams of copper)
- C. Perhaps other non-LCA results , e.g.
 - Energy or waste figures or recycled content
 - Chlorine free or other "frees"









Suggested Impacts Covered

- climate change (carbon footprint),
- depletion of the stratospheric ozone layer,
- acidification of land and water sources,
- eutrophication,
- formation of photochemical oxidants,
- depletion of fossil energy resources, and
- depletion of mineral resources.

Suggested list in ISO 14025

This means we can directly calculate the environmental impacts of a business, product, building



Other Things to Know About the Environmental Product Declaration

Owned by the product or brand owner

Backed up with LCA Studies based on PCRs

Discloses *quantified* life cycle data for the product.

Must clearly state the life cycle stages and product component it covers, the validity over which the label can function.

Must provide contact information for the program owner and the validator.







Environmental Product Declaration

A presentation of quantified environmental life cycle product information for the **Think** work chair in North America.

| | Category | Unit | Total | Materials | Production | Transport | End of Life |
|--------|--------------------|--|-----------|-----------|------------|-----------|-------------|
| | | | | | | | |
| ~ | Global warming | [g CO ₂ -eq.] | 102 610.0 | 67 800.0 | 27 700.0 | 3 720.0 | 3 390.0 |
| 1/1/1/ | Acidification | [g SO ₂ -eq.] | 836.6 | 535.0 | 266.0 | 35.3 | 0.3 |
| dillis | Eutrophication | [g NO ₃ -eq.] | 712.2 | 471.0 | 179.0 | 59.2 | 3.0 |
| | Photochemical smog | [g C ₂ H ₄ -eq.] | 24.2 | 18.0 | 0.8 | 4.6 | 0.7 |





Methyl Ethyl Hydroxy Ethyl Cellulose





| Category of impact | Equivalent unit | Impact | | |
|--|---------------------|-----------|--|--|
| Global warming potential (GWP) | g CO ₂ | 3 200 000 | | |
| Ozone depletion potential (ODP) | g CFC-11 | 9 | | |
| Acidification potential (AP) | mole H ⁺ | 720 | | |
| Photochemical ozone creation potential (POCP) | g ethene | 2700 | | |
| Eutrophication potential (EP) g O ₂ 260 000 | | | | |

Part of the 4-page document



Inventory Information

| Non-renewable resources | | | | |
|-------------------------|-------|------------------------|--------|--|
| Without energy content | kg | With energy content | MJ | |
| Sodium chloride | 1 300 | Natural gas | 34 000 | |
| Limestone | 40 | Nuclear energy | 21 000 | |

This table displays the total us feedstock, needed for 1000 kg

| Renewable resources | | | | |
|---------------------------|----|------------------------|---------|--|
| Without energy content | kg | With energy content | MJ | |
| _ | _ | Biomass | 38 000 | |
| | | Wood | . 8 000 | |


The Wood resource represent Biomass represents the total

| Electricity net consumption | | |
|-------------------------------|-------|--|
| Electricity production source | kWh | |
| Unspecified | 2 600 | |
| Nuclear power | 1 300 | |
| Hydro power | 1 200 | |
| Natural gas | 100 | |
| Coal | 100 | |
| Bio fuel | 100 | |
| | | |

Unspecified means that the electricity grid is not known and is represented by a mix of electricity production sources.











Direct Print Laminate Flooring

What is covered

| Direct print laminate flooring | | | | | |
|--|---------------------------|----------|---------------|-------------|--|
| Evaluation variable | Unit per m² | Total | Manufacturing | End of Life | |
| Primary energy, non renewable | [MJ] | 46.0 | 104 | -57.8 | |
| Primary energy, renewable | [MJ] | 130 | 131 | -0.94 | |
| Global warming potential (GWP 100 years) | [kg CO2 eqv.] | 0.67 | -5.40 | 6.06 | |
| Ozone depletion potential (ODP) | [kg R11 eqv.] | 2.47E-07 | 4.45E-07 | -1.98E-07 | |
| Acidification potential (AP) | [kg SO ₂ eqv.] | 0.036 | 0.022 | 0.014 | |
| Eutrophication potential (EP) | [kg Phosphate eqv.] | 0.0084 | 0.0054 | 0.0030 | |
| Photochemical oxidant formation tential (POCP) | [kg Ethylene eqv.] | 0.0086 | 0.0082 | 0.00042 | |





EPD-EHW-2006221-E

Institut Bauen und Umwelt e.V. www.beu-urrwelt.com





Institut Bouen und Umwelt e.V.



Summary Umwelt-Produktdeklaration Environmental Product-Declaration

| Institut Bauen und Umwelt e.V. | Program holder |
|---|-----------------------------|
| EGGER Floor Products OmbH Im Kissen 19 D – 59029 Brilon | Declaration holder |
| EPD-EHW-2008221-E | Declaration number |
| Egger Floor Products Direct Print Flooring - DPR6 | Declared building products |
| This declaration is an environmental product declaration according to ISO 14025 and describes the environmental rating of the building products lated herein. It is intended to further the development of All relevant en | |
| This validated declaration authorises the holder to beer the official stamps of the institut Bauen und Univert. It only applies to the listed products for three years from the date of listua. The declaration holder is listely for the information and evidence on which the declaration is based. | Validit |
| The declaration is complete and contains in to full form: - Product definition and physical building-related data - declar for any materials and material origin - description of how the product is manufactured - instructions on how to process the product - data on usage condition, unusual effects and end of the phase - life cycle analysis mustas - victions and tests | Content of the declaration |
| 9. April 2006 | Date of issu |
| Wiemmanes | Signature |
| Prof. DrIng. Hond, J. Brossenmayer (President of the notice (Series and Universit) | |
| This declaration and the rules on which it is based have been examined by an independent expert committee (SVA) in accordance with ISO 14005. | Verification of the declara |
| | Signature |
| hear Flows | - Signature |





Summary Umwelt-Produktdeklaration Environmental Product-Declaration

| Direct print flooring is made from decon surface, which are installed as floating if flooring according to EN 15480. The de pressure cylinder. Conundum is added to surface. | foor without give usi consider design is pr | ng a click committed directly or | ection and are deach to the primed coreb | bed as laminate serd using a | Product description |
|---|--|----------------------------------|---|---------------------------------|---------------------------------|
| The applications for the declared direct print laminate flooring are: Interfor areas; laid as floating floor either on poncrate or other existing subfloor such as wood, tile, PVC, etc. A skilled and user can install the flooring thermalous. Due to the low carell thickness the flooring can also be used | | | | | Application |
| scilled and user can initial the flooring to for renovating. | nerseives. Due to t | the low panel to | coness the hooring o | an also be used | |
| The Life Cycle Assessment (LCA) was the Institut Sauen and Ulrawell guideline and data from the "Gel5 4" database we energy production, new material transpo- tion with energy recovery. The direct pri | Scope of the LCA | | | | |
| Direct print laminate flooring | | | | | Results of the LCA |
| Evaluation variable | Unit perm* | Total | Manufactoring | End of Life | |
| Primary energy, non renewable | IMI | 40.0 | 104 | -57.6 | |
| Primary energy, renewable | [M] | 130 | 131 | -0.94 | |
| Global warming potential (GMP 100 years) | [8g:00,eqx] | 0.67 | -5.40 | 6.06 | |
| Ozone depletion potential (OCP) | [ig Rit equ] | 2.476-07 | 4.450.07 | -6.96E-07 | |
| Asidfication potential (AP) | [kg SO, eqv.] | 0.006 | 0.002 | 0.014 | |
| Eutrophication potential (EP) | [kg Phosphate eqv.] | 0.0004 | 0.0054 | 0.0000 | |
| Photochemical oxident formation potential (POCP) | [kg Ethylane eqv] | 0.0006 | 0.0002 | 0.00040 | |
| Prepared by: PE INTERNATIONAL, Lei in cooperation with EGGER Floor Produ | | er, | 注 *** | TENATIONAL | |
| in addition, the results of the following to | ests are shown in the | e environmente | product declaration | andrea 7 | Technological Communication |
| VOC emissions according to Agil Testing institute: eph Entwicklung | | | | ej method | Evidence and verifi- cations |
| Formaldehyde: Teeting institute: WK0 Fraunhofe: | | | | | |
| Toxicity of the fire gases: Testing institute: MFPA Leipzig G | imbili | | | | |
| PCP / Indure Testing institute: WKI Fraunhofer | Withelm-Klaudite-In | with a | | | |





Publisher:

Institut Bauen und Umwelt e.V.

(formerly Arbeitsgemeinschaft Umweltverträgliches Bauprodukt

e.V., AUB) Rheinuferstr 108

53639 Königswinter

Phone: 02223 296679 0

Fax: 02223 296679 1

Email: info@bas-unwelt.com Internet: www.beu-umwell.com

Layout

PE INTERNATIONAL GHIBH

Illustration credits:

EGGER Floor Products GmbH

EGGER Floor Products GmbH

Im Klasen 19 D = 59029 Brillon

the viginal EPD "EPD-EHW-2008221-D"

In the case of a doubt

Contact Information



 EOX (extractable organic halogen compounds).
 Testing institute: MFPA Leipzig GmbH Disable analysis according to DN 36406-4 Testing institute: MFPA Leipzig Grabil



| | Declaration number |
|--------------------------------------|------------------------------|
| | Declared building products |
| d describes the se development of | |
| year 2007. | |
| itut Bauen und | Validity |
| retion is based. | |
| | Content of the declaration |
| | |
| | |
| | |
| | Date of Issue |
| | Signatures |
| | |
| | |
| xendent expert | Verification of the declara- |
| | tion |
| | Signatures |

Although the EPD is compact it covers all the areas required by the standard


Including Verification





Verifiers

- Independent
 - Uninvolved with work
 - No conflict of interest
- Competent
 - LCAs & EPDs
 - Standards & regulations
 - Product





Verification of EPD

- Conformance with the PCR & PCR Program;
- Conformance with the ISO 14040 series of standards;
- that data evaluation is comprehensiveand complete

- Completeness and Accuracy of
 - The LCA data;
 - The additional environmental information;
 - The supporting information.



International Standards that Apply







- ISO 14020 (Environmental Labeling)
- ISO 14025 (Type III Environmental declarations)
- ISO 21930 (EPDs for buildings)
- ISO ISO/TC 207/SC 3 N284 Guidelines for Making and Assessing Environmental Claims
- ASTM- international standardization underway
- EU CEN Standardization underway

National Standards that Apply

Mandator

Mandatory

- In The U.S. Part 260 Guides for the Use of Environmental Market Claims (Federal Trade Commission)
- In Canada, voluntary guidance per "Plus 14021"
 - France has AFNOR standards under le *Grenelle* Environnment
- PAS 2050 Carbon footprinting (British Standards Institute)
- And so forth...
- Standardization effort underway at the Leonardo Academy





Questions?





Amy Costello



- Senior Environmental Scientist, Armstrong
 World Industries
- Leading PCR standards development within ASTM International



What are Product Category Rules?

Product Category Rules:

⇒ Set of specific rules, requirements and guidelines for developing Type III environmental declarations (EPD) for one or more product categories.


Product Category:

⇒ Group of products that can fulfill equivalent functions



Source: ISO 14025 (2006)

ISO 21930 (2007)



PCR: Specify common goal and all relevant rules for product category LCA, predetermined parameters, rules on additional environmental information, requirements for reporting. Wrlte Instructions on how to produce the data required for the declaration.



Why Product Category Rules?

Comparability
Modularity
Transparency
Flexibility





Comparability



- Allows environmental performance of products to be compared on a life cycle basis
- Information must be transparent to allow understanding of limitations of comparability

Limits:

- Based on same PCRs
- Based on all life cycle stages





Modularity

- LCA based data
- For materials, parts and other inputs
- Used in the manufacture/assembly of other products

Information Modules

- Compilation of data
- Basis for an EPD covering a unit process or a combination of unit processes that are part of the life cycle of a product
- Should cover all life stages (ISO 14025)
- May be a Type III EPD



Transparency

- General Program Instructions
- A list of all published PCR documents within the program
- PCR documents
- Involvement of interested parties
- "Open" consultation recommended





Flexibility

 Allows a range of different types of bodies to operate a Type III EPD programs



- Use of relevant stages of the life cycle, with documentation
- Allows for additional information



Product Category Rules

- Created by the Program Operator
- A separate PCR for each functional unit
- Contains all the scoping required by an LCA
- Also scoping of EPD-specific issues such as:
 - The format of the label
 - Information about the program and the verifier



What does the program operator do?

Develops a management program to produce EPDs

Specifies rules and criteria for verifying PCRs/EPDs

Assures Program:

- Includes interested parties in development of the program and PCRs
- Is transparent, available, kept current and adhered to
- Follows all the relevant ISO standards

Operator may or may not do EPD studies



Program Operators

- Can be any organization or group of organizations
- Examples:
 - EPD Network *(EU, mostly Sweden)
 - Japanese Ecoleaf
 - IBU Germany
 - Eco-Product Institute Korea
 - IERE Earthsure









* United Nation's Classification Registry CPC codes



How is information Shared?

- Up to the Program Operators
- Swedish & Germany Systems have MOU and share PCRs
- EPD (Sweden) Allows all PCR to be posted to their website
- GEDnet Global network that foster cooperation and information exchange among program operators (www.gednet.org)





What is included in PCR?


- Product Category Definition
- Goal and Scope definition for the product LCA
 - Functional unit
 - Declared unit
 - System boundary
 - Description of data
 - Units
 - Criteria for the inclusion of inputs and outputs





What is included in PCR?

- Inventory Analysis data collection & allocation
- Impact category selection and calculation rules
- Additional environmental information
- Materials and substances for declaration
- Period of validity





How to develop PCRs?

- Gather previous PCRs and LCAs on the topic
- Get interested parties together
 - Manufacturer
 - Trade Association
 - Competitors
 - Material suppliers
 - NGOs
 - Others








How to develop PCRs?

- Identify the system function and functional unit
- If necessary develop the LCA
- Write the PCR based on existing LCA(s)
- Have a panel review the PCR







Levels of Verification

- General Type III Program
 - Independently verified internally or externally
 - ISO 14020 and 14040 series
- PCR Review
 - Third-party reviewed
- Data (LCA, LCI) Verification
 - Independently verified
- Type III EPD
 - Independent verified Business to business
 - Third Party Business to consumer





What are the verification procedures?

PCR Review:


- Third-party Panel: chair and two members
- Demonstrates:
 - PCR compliance with ISO 14040
 - PCR give a description of the environmental aspects of a product
- Review and responses must be included in PCR documentation







The sequence of documents from the PCR document to the





Questions?





ISO 21930 Sustainability in building construction

Environmental declaration of building products

INTERNATIONAL STANDARD

ISO 21930

> First edition 2007-10-01


Sustainability in building construction — Environmental declaration of building products

Bâtiments et ouvrages construits — Développement durable dans la construction — Déclaration environnementale des produits de construction



ISO 21930

- EPD for Building Products
 - Provides PCR Framework
 - Very similar to 14025
 - Introduces
 Reference Service
 of Building
 Products over life
 of Building
 - Cradle to gate information modules for B2B





ISO 21930 – Impact Categories

- 8.2.2.1 Environmental impacts expressed in terms of the impact categories of LCIA
 - climate change (greenhouse gases);
 - depletion of the stratospheric ozone layer;
 - acidification of land and water sources;
 - eutrophication;
 - formation of tropospheric ozone (photochemical oxidants).

Essentially the same list as in ISO 14025



Standardization of Sustainable Construction

ISO TC 59 SC 17

- ISO 15392: Sustainability in building construction General principles
- ISO TS 21929: Sustainability in building construction Sustainability indicators
 - Part 1: Framework for the development of indicators for buildings
- ISO 21930: Sustainability in building construction Environmental declaration of products
- ISO 21931: Sustainability in building construction -- Framework for methods of assessment
 - for environmental performance of construction works -- Part 1: Building

ISO TC 59 SC 14

- ISO 15686: Buildings and constructed assets Service life planning
 - Part 1: General principles
 - Part 5 Life cycle costing
 - Part 6: Procedures for considering environmental impacts
 - Part 8: Reference service life and service life estimation.

CEN TC 350: Sustainability of construction works

- prCEN/TS 15643 1-4: Framework for assessment of integrated building performance –
 Part 1: Environmental, health and comfort and life cycle cost performances
- WI 350002: Assessment of environmental performance of buildings Calculation methods
- WG2: Building Life Cycle Description
- prEN 15804: Environmental product declarations Product category rules
- WI 350005: Environmental product declarations Communication formats
- WI 350006: Environmental product declarations Methodology and data for generic data



A lot of activity to develop sustainable construction standards

Standard Summary

- ISO 14040 and 14044 set-up LCA calculation rules
- ISO 14025 and 21930 describe procedures to develop Product Category Rules, for their open consultation, review, approval and publication
- ISO I4025 for setting up the rules for independent verification
- ASTM Standard (WK23566) will complete these rules by providing specific data quality requirements, data sources,

ASTM Work Item

ISO 14025/ISO 21930

ISO 14040/ISO 14044



Generic

Competence of Verifiers

Program Operators establish minimum requirements for competence of verifiers

- Expertise in LCA and methodology for LCA
- Knowledge of sector
- Process and product knowledge
- Knowledge of relevant standards
- Knowledge of Type III requirements





Independence of Verifiers and PCR Panel

Independent Verifiers (Internal or External):

- No involvement in the LCA or EPD
- No conflicts of interest





Rules for data confidentially

Product-specific data are confidential because of

- Competitive business requirements
- Proprietary information covered by intellectual property rights
- Similar legal restrictions





France



- Grenelle de l'Environnement Law (2007) – omnibus legislation
- All high volume consumer products sold in France have an EPD effective 1/1/11
- Anticipate that the program will spread to all of the EU
- Plastics Europe EPDs already available





Technical Barriers to Trade



Safety & Environmental Laws & regulations based on International Standards are assumed not to be barriers to trade







Carbon Footprint Program in Japan

Sample of Carbon footprint



| Γ | Enterprise | KOKUYO S&T Co.,Ltd. | | | |
|---|------------------------------------|--|--|--|--|
| | Product of the carbon footprint | Pipe Type File, "EcoTwin-R", (7-RT650B), | | | |
| (| Quantity | A4-size, Paper Capacity; 5cm | | | |



カーボンフットブリント暫定表示 Provisional mark for

EcoProducts 2008 Exhibition

| Stage | Material Producti on | Product Manufac turing | Transpor tation | Retailing | Usage | Disposition /Recycling | Total | | |
|---|---|------------------------------|-----------------|-----------|-------|---------------------------|-------|--|--|
| GHG Emission g-CO ₂ /P | 1003.8 | 27.3 | 50.9 | 155.9 | 0 | 99.5 | 1337 | | |
| Calculati on condition | -The GHG emission in Material Production Stage was calculated using design weight and secondary data prepared by the secretariat, where loss ratio of sheet type material was considered. -The GHG emission in Retailing Stage was calculated using given value of GHG per sales price, which was prepared by the secretariat. | | | | | | | | |
| | -The GHG emission in Usage Stage was identified as zero due to no energy consumption in this stage. | | | | | | | | |





Walmart *


- LCA is the basis of its sustainability program
- Using LCA in Packaging Program now
 - Data on every single package
- Planning EPD with a sustainability index for all products





Carbon Footprinting Proposed in U.S. Legislation

- HR 3543 (carbon disclosure)
- HR 2454 (American Clean Energy and Security Act) – Passed
- Senate 1733 (Energy Bill) in committee



Bottom line: carbon footprinting is coming to the U.S.



Step towards PCRs in the U.S.

- Pilot Project to build infrastructure for PCRs
 - Invited Workshop, November 4-5, in Seattle
 - Jointly sponsored by EPA
 Region X and the Institute for
 Environmental Research and
 Education
- Goal to discuss and plan for an infrastructure for PCRs for building components.







Interested Parties

































ACLCA

















Questions?





